

MFIRE





VERSATILITY

OVER 300 POSSIBLE COMBINATIONS

Nova Series brings the ultimate versatility to the hearth industry. With over 300 possible combinations between firebox size, door color, configuration, and accessories, Nova Series can fit virtually any style in any setting.







Check out all of
Nova Series' versatility
and the many options
it provides with the
QR code above.



NOVA SERIES

VERSATILITY MENU

STEP 1 CHOOSE A FIREBOX











NOVA

NOVA 2

NOVA 3

STEP 2 CHOOSE A DOOR







CHARCOAL



STAINLESS STEEL

STEP 3 CHOOSE A CONFIGURATION









STEP 4 CHOOSE ADDITIONAL ACCESSORIES

• LEG KITS: 3", 6", 9"

- ASH LIP
- REDUCED CLEARANCE KITS
- ASH PAN

BLOWER

MAKE-UP AIR KIT

NOVA SERIES

FREE STANDING | TOWER | INSERT | BENCH





FREE STANDING



NOVA

PERFORMANCE

Heating Capacity: Up to 1,500 ft²

Max. Heat Output: 50,000 BTU/hr

Max. Efficiency: 79%

EPA Emissions: 1.9 g/hr

Firebox: 1.7 ft³

Stove Dimensions: 24" H x 22.5" W x 18.5" D

Glass Dimensions: 12.25" H x 14.25" W

Blower (Optional): 125 CFM

15+ Hour No-Match Restart



NOVA 2



PERFORMANCE

Heating Capacity: Up to 2,500 ft²

Max. Heat Output: 75,000 BTU/hr

Max. Efficiency: 81%

EPA Emissions: 1.9 g/hr

Firebox: 2.4 ft³

Stove Dimensions: 26.5" H x 27" W x 18.5" D

Glass Dimensions: 13.75" H x 17.75" W

Blower (Optional): 125 CFM

17+ Hour No-Match Restart



NOVA 3



PERFORMANCE

Heating Capacity: Up to 3,000 ft²

Max. Heat Output: 100,000 BTU/hr

Max. Efficiency: ---

EPA Emissions: ---

Firebox: 3.2 ft³

Stove Dimensions: 26.5" H x 27" W x 23" D

Glass Dimensions: 13.75" H x 17.75" W

Blower (Optional): 125 CFM

19+ Hour No-Match Restart

COMING SOON. ETA FALL 2022

Simple and Easy to Use

Nova is designed to take the guess work and tinkering out of wood burning. Perfect for both the causal wood burner and lifelong burner, there is no longer a need to adjust burn settings. Nova runs on cruise control, meaning you don't need to make adjustments. This allows you to sit back and enjoy a clean, efficient, and beautiful fire.

Easy Hearth Mount Installations

Nova's top and rear vent capability sets it up for easy hearth mount installations. Adding a contemporary touch to a traditional look, allowing for true warmth of a wood stove while never compromising the beauty of your existing fireplace.

Focus on the Fire

Nova's viewing area mimic's the size of the firebox allowing for an intimate experience every time. Up to 245 in² of glass showcases the beauty and warmth that a wood fire brings.



Nova Tower is the natural evolution of Nova. Still designed to take the guess work and tinkering out of wood burning but offering easier loading and built-in wood storage. Perfect for both the casual wood burner and lifelong burner, there is no longer a need to adjust burn settings. An easy-to-install ash drawer not only serves a practical use, but also completes the look fitting seamlessly with the modern aesthetic expected with the Nova Series. Simply load the stove, light a match, and enjoy the flames.



NOVA TOWER

Dimensions: 43" H x 22.5" W x 18.5" D

Firebox: 1.7 ft³

Blower (Optional): 125 CFM

Storage: 4+ Wood Loads

NOVA 2 TOWER

Dimensions: 45.5" H x 27" W x 18.5" D

Firebox: 2.4 ft³

Blower (Optional): 125 CFM

Storage: 5+ Wood Loads







moent

Nova Insert brings the perfect modern design with the performance that Nova has been built on. With its large viewing area and minimal trim, it's easy to focus on the beauty of the fire. Enjoy a fire that is efficient and clean from a modern take on the traditional fireplace without the need to make any adjustments. Just light a fire and let Nova take care of the rest.

NOVA INSERT

Minimum Fireplace Dimensions: 25" H x 30" W x 16" D

Trim Kit: 29" H x 40" W

Firebox: 1.7 ft³

Blower: 105 CFM



NOVA 2 INSERT

Minimum Fireplace Dimensions: 28" H x 33" W x 16" D

Trim Kit: 32" H x 44" W

Firebox: 2.4 ft³

Blower: 105 CFM





BENCH

Nova Bench offers a new and unique setting to view the large, beautiful fires that the Nova Series has been built on. Compatible for both the Nova and Nova 2, our bench provides an elevated viewing area, allowing for easier reloading, with ample storage space below. The sleekness and simplicity of operation is the latest example of Nova Series' versatility.



NOVA BENCH

Bench Dimensions: 18.5" H x 48" W x 16" D

Firebox: Both Nova & Nova 2

Blower (Optional): 125 CFM

Storage: 5+ Wood Loads

BEAUTIFUL WOOD STOVES FOR MODERN LIVING



HEATING FOR A CAUSE





Working on behalf of the American public, the National Forest Foundation leads forest conservation efforts and promotes responsible recreation. We believe these lands, and all they provide, are an American treasure and are vital to the health of our communities.

Through MF Fire's partnership with the National Forest Foundation, we assist in planting native, ecologically appropriate trees at the cost of just \$1 per tree.

A proud small business partner of the

50 MILLION FOR FORESTS

National Forest Foundation nationalforest.org

National Forests and Grasslands provide 193 million acres of wildlands across the country.

- More than 9,000 miles of scenic byways
- · Nearly 150,000 miles of hiking trails
- More than 4,400 miles of wild & scenic rivers
- At least 5,100 campgrounds

50 Million For Our Forests

Our reforestation campaign continued to address critical reforestation needs on our National Forests to ensure healthy forests for future generations to come.

7.3M

Trees Planted in 2021

25+

Tree Species

21,000+
Acres Reforested

Supporting Our National Forests

Navigating changing conditions, we continued to work closely with the U.S. Forest Service and our partners to complete critical projects.

14.2M

NFF Funds Invested


\$7.4M


Funds Leveraged


\$21.6M Total Project Value





NOVA SPECIFICATIONS














NOVA


| Height with 3" legs | 24" |
|-----------------------------------|--------|
| Width (w/o bypass) | 22.5" |
| Width (w/ bypass) | 23.6" |
| Depth w/ 4" ash lip | 22" |
| Depth w/o 4" ash lip | 18.5″ |
| Side to center of flue collar | 11.25" |
| Height to center rear flue collar | 19" |
| Back to center top flue collar | 6.25" |

NOVA TOWER

| Height with tower | 43" |
|-----------------------------------|--------|
| Width (w/o bypass) | 22.5" |
| Width (w/ bypass) | 23.6" |
| Depth | 18.5" |
| Side to center of flue collar | 11.25" |
| Height to center rear flue collar | 38″ |
| Back to center top flue collar | 6.25" |

NOVA INSERT

| 29″ |
|-------|
| |
| 40" |
| 30″ |
| 25" |
| 16" |
| 4.25" |
| |



MINIMUM CLEARANCE REQUIREMENTS

| | | Single Wall Connector Pipe | Double Wa Connector Pi | |
|---|--------------------------|-------------------------------|---------------------------|-----|
| А | Sidewall to unit | 20" (508 mm) | 18" (458 mn | n) |
| В | Backwall to unit | 17" (432 mm) | 11" (280 mm | ٦) |
| С | Sidewall to connector | 28" (711 mm) | 26" (661 mn | n) |
| D | Backwall to connector | 20" (508 mm) | 14" (356 mn | n) |
| Е | Corner to unit | 12" (305 mm) | 9.5" (241 mr | n) |
| F | Corner to connector | 21" (534 mm) | 18.5" (470 m | m) |
| G | Sidewall to unit | 20" (508 mm) | | |
| Н | Backwall to unit | 13.5" (343 mm) | | |
| | Sidewall to connector | 28" (711 mm) | | |
| J | Backwall to connector | 13.5" (343 mm) | FLOOR PRO | OTE |
| K | Top of unit to ¾" trim | 8" (203 mm) | Leg | |
| L | Top of unit to 8" mantel | 11" (280 mm) | Height | - |
| | Floor Protection | | 3" | F |
| М | Front | 16" US/18" CAN | 6" | |
| N | Side | 8" (203 mm) | 9" | |

2" (51 mm)

Chimney Connector

FLOOR PROTECTION REQUIREMENTS

Double Wall

Connector Pipe with

Reduced Clearance Kit

20" (508 mm) 7.5" (190 mm)


28" (711 mm)


11" (280 mm)


9.5" (241 mm) 18.5" (470 mm)


| Leg Height | With Ash Lip | Without Ash Lip |
|---------------|-----------------|--------------------|
| 3″ | R = 1.35 | R = 1.35 |
| 6″ | Type 1 | R = 1.35 |
| 9″ | Type 1 | Type 1 |
| Tower | Type 1 | Type 1 |


NOVA 2 SPECIFICATIONS














NOVA 2


| Height with 3" legs | 26.5" |
|-----------------------------------|--------|
| Width (w/o bypass) | 27" |
| Width (w/ bypass) | 27.83" |
| Depth w/ 4" ash lip | 22" |
| Depth w/o 4" ash lip | 18.5″ |
| Side to center of flue collar | 13.5″ |
| Height to center rear flue collar | 21.5" |
| Back to center top flue collar | 6.25″ |

NOVA 2 TOWER

| Height with tower | 45.5″ |
|-----------------------------------|--------|
| Width (w/o bypass) | 27" |
| Width (w/ bypass) | 27.83" |
| Depth | 18.5″ |
| Side to center of flue collar | 13.5″ |
| Height to center rear flue collar | 40.5″ |
| Back to center top flue collar | 6.25″ |

NOVA 2 INSERT

| Surround height | 32" |
|-----------------------------------|-------|
| Surround width | 44" |
| Minimum fireplace width | 33" |
| Minimum fireplace height | 28" |
| Minimum fireplace depth | 16" |
| Back to center top flue collar | 4.25" |



Double Wall

Connector Pipe

20" (508 mm)

14" (356 mm)

29" (736 mm)

17" (432 mm)

9" (229 mm)

18" (457 mm)

MINIMUM CLEARANCE REQUIREMENTS

| | | Single Wall Connector Pipe |
|---|---------------------------|-------------------------------|
| А | Sidewall to unit | 22" (559 mm) |
| В | Backwall to unit | 20" (508 mm) |
| С | Sidewall to connector | 31" (787 mm) |
| D | Backwall to connector | 23" (584 mm) |
| Е | Corner to unit | 14" (356 mm) |
| F | Corner to connector | 23" (585 mm) |
| G | Sidewall to unit | 22" (559 mm) |
| Н | Backwall to unit | 16" (406 mm) |
| | Sidewall to connector | 31" (787 mm) |
| J | Backwall to connector | 16" (406 mm) |
| K | Top of unit to ¾" trim | 10" (254 mm) |
| L | Top of unit to 10" mantel | 14" (356 mm) |
| | Floor Protection | |
| М | Front | 16" US/18" CAN |
| N | Side | 8" (203 mm) |
| 0 | Chimney Connector | 2" (51 mm) |

FLOOR PROTECTION REQUIREMENTS

Double Wall

Connector Pipe with

Reduced Clearance Kit

22" (508 mm)

9" (228 mm)

31" (787 mm)

12.5 (318 mm)

9" (229 mm)

18" (457 mm)

| Leg Height | With Ash Lip | Without Ash Lip |
|---------------|-----------------|--------------------|
| 3″ | R = 1.35 | R = 2.0 |
| 6″ | Type 1 | R = 1.35 |
| 9″ | Type 1 | Type 1 |
| Tower | Type 1 | Type 1 |



MFFIRE

Here at MF Fire, we take a different approach when creating wood stoves. We started MF Fire to deliver the best wood heat, while using innovation to eliminate the undesirable

aspects of wood stoves. We leverage our patented technologies, intelligent design, and state of the art fire science to build stoves with high efficiency and low emissions, while

providing users with a simple, easy-to-use experience.

We love wood heat, but wood stoves haven't changed much in decades. In modern times, there is no reason a wood stove should be polluting, inefficient or difficult to use.

With designs that fit any home, whether a cabin, chalet, farm house, or modern home, our timeless and contemporary wood stoves deliver beautiful aesthetics to fit any taste.

You only purchase a wood stove once every 10-20 years and deserve an attractive stove that you enjoy looking at, while having it deliver all your heating needs. We use only the finest quality materials and expert craftsmanship. Starting with welded steel, our wood stoves employ large glass viewing windows and a friendly user experience that delivers endless hours of wood heat enjoyment. We produce wood stoves unlike any others in North America that range from sleek and modern to sophisticated and high tech.

Wood is a sustainable and renewable source of fuel and heat that should be responsibly utilized to create clean energy. We are committed to creating and producing wood stoves that meet the demands of modern living.